

TECHNICAL DATA

VIDAFLEX® 560 - Braided Glass Sleeving Silicone Elastomer Coated

DESCRIPTION

Braided 'E' glass insulating sleeving with silicone elastomer coating. VIDAFLEX® S560 insulating sleeveings offer a high degree of flexibility and provide good resistance to ozone, ultraviolet radiation and humidity, as well as excellent electrical, thermal and mechanical protection.

APPLICATIONS

- Wiring harnesses
- Class H rated rotating machines
- Household appliances
- Lighting
- Class H rated transformers
- Automotive

PHYSICAL PROPERTIES

Thermal rating (IEC 60085)	Class H (180°C)
Maximum short-term temperature	250°C
Dielectric strength @ 20°C (IEC 684-2)	6.0kV/1 min
Dielectric strength @ 20°C (ASTM D-350)	7.0kV
Breakdown voltage @ 20°C (IEC 60085)	≥ 7.0kV
Flammability	Self extinguishing

STANDARD DIMENSIONS (EN 60684-2)

Bore Size mm	Tolerance on Bore Size mm	Nominal Wall Thickness mm	Approximate Weight g/m
6.0	± 0.25	1.00	33
7.0	± 0.25	1.00	40
8.0	± 0.25	1.00	48
10.0	± 0.30	1.00	65
12.0	± 0.30	1.00	83
16.0	± 0.40	1.00	117
20.0	± 0.50	1.00	155

SUPPLY FORMATS

Cardboard reels	50, 100, 250, 500m, depending on bore size
Cut lengths	On request
Standard colours	Black

® Registered trademark

Statements, technical information and recommendations contained herein are based on tests we believe to be reliable but they are not to be construed in any manner as warranties expressed or implied. The user shall determine the suitability of the product for their intended use and the user assumes all risk and liability whatsoever in connection therewith.