

TECHNICAL DATA

PAR TURBINE OILS

DESCRIPTION

PAR Turbine Oils are a range of high specification oils, manufactured from a blend of solvent refined mineral oil, with a multi-purpose turbine oil additive package.

FEATURES

PAR Turbine Oils are fully inhibited turbine oils.

PERFORMANCE SPECIFICATIONS

PAR Turbine Oils conform to the following specifications:

| | |
|---------------------|------------------------|
| AFNOR E 48-600 HM46 | Hagglunds-Denison HF-2 |
| DIN 51524 Part 2 | BS 4231 |

TYPICAL PHYSICAL PROPERTIES

| Grade | 32 | 46 | 68 |
|----------------------------|-------|-------|-------|
| ISO Viscosity Grade | 32 | 46 | 68 |
| Kinematic viscosity @ 40°C | 32 | 46 | 68 |
| Specific gravity @ 15.6°C | 0.870 | 0.870 | 0.875 |

PACKAGING & SUPPLY

- Bulk tanker delivery
- IBC (1,000 Litres approx)
- 205 Litres
- 25 Litres

HEALTH & SAFETY

Please refer to Material Safety Data Sheet (MSDS).

PAR Turbine Oils are not classified as dangerous under current UK Health & Safety & Environmental Legislation when used for the application for which it is intended.